

STRUCTURAL, ELECTRO-MAGNETIC AND ELECTRICAL ANALYSIS IN
MONOVALENT DOPED $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ MANGANITES

SUFIA AQILAH BINTI RAZALI

A thesis submitted in
fulfillment of the requirement for the award of the
Degree of Master of Science

Faculty of Applied Sciences and Technology
Universiti Tun Hussein Onn Malaysia

SEPTEMBER 2019

ACKNOWLEDGEMENT

In the name of Allah, the Most Gracious and the Most Merciful. Alhamdulillah, all praises to Allah for giving me the opportunity to complete this Master's Degree Project which is title "Structural, electro-magnetic and electrical analysis in monovalent doped $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ manganites" that can be complete within the prescribed time frame. This project was compulsory for Master's student to complete the postgraduate program that lead to fulfillment the requirement of Master's Degree in Science .

First and foremost, my deepest gratitude goes to my supervisor, Dr. Suhadir Shamsuddin for his support, guidance, tutoring and supervision. His dedication and keen interest above all his overwhelming attitude to help me a lot to the accomplishment of this project. Without his patience, I won't be able to see positive things and ability inside of me. I also want to send my gratitude to Dr Norazila Ibrahim as my co-supervisor for her guidance and helping to finished my project.

Most importantly, my sincere appreciation and special thanks to my family for their continuous support and encouragement especially to my beloved mother, Mrs Kelsom Bahari. This project wouldn't be completed without their constant prayers, patience and endless love.

Last but not least, sincere thanks to my beloved friends, Nurul Nasuha Khairulzaman, Norasikin M Nasar and Bibi Zulaika Bhari for their kindness, supportive advice and moral support during my study. Thanks for all those memories and friendship. To those who indirectly contributed in this project, your kindness means a lot to me. Thank you very much.

ABSTRACT

The polycrystalline $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{Mn}_1\text{O}_3$ ($x = 0, 0.05$ and 0.10) samples were prepared using solid state reaction method. K doped manganites have been investigated to study its effect on crystalline phase and surface morphology as well as electrical transport and magnetic properties. However most of study show inconsistent result regarding to the electrical transport and magnetic properties as well as crystalline phase and morphology study. Thus, further detailed study need to be conducted in order to explain the properties of manganites. The structured properties of the $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ manganite have been characterized using X-ray diffraction measurement showing the crystalline phase of samples were single phased and indexed as orthorhombic structure (*Pnma* space group). The morphological study from scanning electron microscope showed that there were improvements on the grains boundaries and sizes as well as the compactness with K doping. On the other hand, DC electrical resistivity measurement showed all samples exhibit insulating behavior. Analysis of $\text{dln}\rho/\text{d}T^{-1}$ vs. T revealed a peak at temperature 210K for $x = 0$ and the peaks were shifted to the lower temperature around 190 K and 165 K for $x = 0.05$ and $x = 0.1$ respectively. Meanwhile, the investigation on magnetic behavior showed all samples exhibit transition from paramagnetic phase to anti-ferromagnetic phase with decreasing temperature and the T_N was observed to shift to lower temperature. Apart from that, the electrical analysis; variable range hopping (VRH) model was selected in order to explain the electrical behavior of the samples as the value of R^2 is approached to 0.9999 as it has highest value compared to small polaron hoping (SPH) model. In conclusion, the effect of K^+ doped on $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{Mn}_1\text{O}_3$ were effected the properties of manganites including the structure, surface morphology, magnetic and electrical due to the different ionic radius and reduction in the distortion of MnO_6 octahedral.

ABSTRAK

Kaedah yang digunakan untuk menyediakan bahan campuran kristal $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ ($x = 0, 0.05$ dan 0.10) adalah kaedah reaksi keadaan pepejal. Campuran K kedalam manganites telah dilakukan untuk mengkaji kesan campuran pada fasa kristal dan permukaan morfologi serta ciri-ciri pengangkutan elektrik dan sifat magnetik manganites. Walau bagaimanapun, kebanyakan kajian tidak menunjukkan keputusan yang stabil berhubung ciri-ciri pengangkutan elektrik dan sifat magnetic, begitu juga dengan fasa kristal dan permukaan morfologi. Justeru, kajian yang menyeluruh harus dilakukan untuk menerangkan ciri-ciri manganite ini. Sifat-sifat struktur komponen $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ telah dicirikan dengan menggunakan pengukuran pembelauan sinaran-X (XRD) dan terbukti bahawa fasa kristal sampel pada dasarnya bertahap tulen dan struktur adalah berbentuk orthorhombik (kumpulan kelas $Pnma$). Kajian morfologi permukaan dari Microskop electron pengimbasan menunjukkan terdapat peningkatan pada sempadan butir dan saiz serta kekompakan dengan peningkatan K. Sebaliknya, pengukuran kerintangan elektrik arus terus menunjukkan semua sampel bersifat penebat. Analisis $\ln \rho / dT^{-1}$ vs T menunjukkan wujudnya puncak yang jelas dan dapat dilihat pada suhu 210K untuk $x = 0$ dan menurun ke suhu lebih rendah sekitar 190 K ($x = 0.05$) dan 165 K ($x = 0.1$). Sementara itu, kajian terhadap sifat magnet menunjukkan berlakunya peralihan fasa dari fasa paramagnetik kepada fasa anti-ferromagnetik dengan suhu berkurangan untuk semua sampel, dan T_N beralih kepada suhu yang lebih rendah. Di samping itu, analisis data elektrik, *variable range hopping* (VRH) telah dipilih untuk menjelaskan ciri-ciri elektrik pada sampel kerana nilai R^2 lebih menghampiri nilai 0.9999 berbanding *small polaron hopping* (SPH). Oleh itu, kesan daripada K doping didalam campuran $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ mempengaruhi ciri ciri manganites termasuk fasa kristal dan permukaan morfologi serta ciri-ciri pengangkutan elektrik dan sifat magnetik disebabkan pengurangan penyimpangan MnO_6 oktahedral.

CONTENT

TITLE	i
DECLARATION	ii
ACKNOWLEDGEMENT	iii
ABSTRACT	iv
ABSTRAK	v
CONTENT	vi
LIST OF TABLES	ix
LIST OF FIGURES	x
LIST OF SYMBOLS & ABBREVIATIONS	xiii
LIST OF PUBLICATIONS	xv
CHAPTER 1	INTRODUCTION
1.1	Background of study 1
1.2	Problem statement 3
1.3	Objectives of study 4
1.4	Scope of study 4
1.5	Significant of study 5
CHAPTER 2	LITERATURE REVIEW
2.1	Introduction 7
2.2	Structure of ceramic 9
2.2.1	Crystal structure 9
2.2.2	Crystal lattice 10
2.2.3	Perovskite structure 11
2.3	Interaction in magnetic compound 12
2.3.1	Colossal Magnetoresistance (CMR) effect 12
2.3.2	Jahn Teller effect 13
2.3.3	Double exchange mechanism 15
2.3.4	Charge ordering 15

2.4	Solid-state reaction in preparing of manganites	16
2.5	Research on manganites	18
2.5.1	Effect of monovalent doped in manganites compound	19
2.5.2	Effect of divalent doped in manganites compound	22
2.5.3	Electrical analysis	27
CHAPTER 3	METHODOLOGY	31
3.1	Introduction	31
3.2	Sample preparation	32
3.3	Sample characterization	36
3.3.1	X-ray diffraction (XRD) measurement	36
3.3.2	Bulk density and porosity	39
3.3.3	Scanning electron microscope analysis	41
3.3.4	AC Susceptibility measurement	43
3.3.5	DC electrical resistivity measurement	45
3.3.6	Electrical analysis	48
CHAPTER 4	RESULTS AND DISCUSSION	51
4.1	Introduction	51
4.2	Influence of K^+ ion doping on structure of $Nd_{0.75}Na_{0.25-x}K_xMnO_3$	51
4.3	Observation on surface morphology of $Nd_{0.75}Na_{0.25-x}K_xMnO_3$ manganites	54
4.4	Effect of K^+ doped on the electrical and magnetic properties	56
4.5	Electrical analysis of $Nd_{0.75}Na_{0.25-x}K_xMnO_3$ manganites	58

CHAPTER 5	CONCLUSION AND RECOMMENDATIONS	63
5.1	Introduction	63
5.2	Conclusion	63
5.3	Recommendations	64
REFERENCES		66
APPENDIX		72
VITA		



LIST OF TABLES

2.1	Type of doping compound from the previous study	26
3.1	Composition of $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$	31
3.2	Properties of chemical substances	32
4.1	Lattice parameter (\AA), unit cell volume, V (\AA^3), density, D (g/cm^3), charge-ordering temperature, T_{CO} (K) and Neel temperature, T_N (K) of $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ ($x = 0, 0.05$ and 0.10)	53
4.2	The square of the linear correlation coefficient (R^2) value for $x = 0 - 0.10$ samples	61
4.3	Parameters obtained from variable range hopping (VRH) model fitting in the insulating region for $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ ($x = 0 - 0.10$) samples	61

LIST OF FIGURES

2.1	Stable and unstable anion-cation coordination configurations	10
2.2	Schematic representation lattice parameters of a cubic unit cell	10
2.3	Structure of Perovskite	12
2.4	Jahn Teller distortion for an d^9 octahedral transition metal complexes	14
2.5	Double exchange mechanism	15
2.6	Particle changes during Sintering Process	17
2.7	Lattice parameter, unit cell volume and XRD patterns of $\text{Pr}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ compounds with $x = 0$ to $x = 0.20$	19
2.8	The scanning electron microscope micrograph (3 kX) of $\text{Pr}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ for ($x = 0 - 0.20$) manganites compound	20
2.9	XRD pattern $\text{La}_{0.8}\text{Ba}_{0.1}\text{Ca}_{0.1}\text{Mn}_{0.8}\text{Co}_{0.2}\text{O}_3$. Inset shows the Crystal Structure and The Coordination Polyhedron of Mn	22
2.10	Temperature dependence of the electrical resistivity of NCMCrO. Inset the $\text{dln}\rho/\text{d}T^{-1}$ versus T plot	24
2.11	Temperature dependence of DC conductivity of $\text{Pr}_{0.7}\text{Ca}_{0.3}\text{MnO}_3$ and $\text{Pr}_{0.7}\text{Ca}_{0.3}\text{MnCo}_{0.1}\text{O}_3$ samples	25
2.12	Fitting of experimental data for $x = 0.05$ sample with equation Eq.(2.2) and Eq.(2.3)	28

2.13	Plot of $\ln \rho$ versus $T^{-1/4}$ for $\text{La}_{0.85}\text{Ag}_{0.15}\text{MnO}_3$ ($x = 0 - 0.15$) in zero field and under external magnetic field of 0.7T. The solid lines show the fitting made to $\rho = \rho_{0m} \exp (T_{0m}/T)^{1/4}$	29
3.1	Temperature profile of calcination process	34
3.2	Temperature profile of sintering process	34
3.3	Process for sample preparation of $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ ($0 \leq x \leq 0.10$) samples	35
3.4	Diffraction of X-ray by planes of atom	36
3.5	Interference illustration	37
3.6	XRD Bruker D8 Advance	39
3.7	Density kit model Mettler Toledo	40
3.8	Working principle SEM	42
3.9	Scanning electron microscope Hitachi SU1310	43
3.10	Schematic diagram for AC susceptibility	44
3.11	AC susceptibility measurement equipment	45
3.12	Four-point-probe method	47
3.13	Schematic diagram of the electrical resistivity measurement system	47
3.14	DC electrical resistivity measurement equipment	48
4.1	Powder X-ray diffraction pattern for $\text{Nd}_{0.75}\text{Na}_{0.15-x}\text{K}_x\text{MnO}_3$	52
4.2	SEM micrographs of $\text{Nd}_{0.75}\text{Na}_{0.15-x}\text{K}_x\text{MnO}_3$ sample (a) $x=0$ (b) $x = 0.05$ (c) $x = 0.10$	55
4.3	Temperature dependence of electrical resistivity for $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ ($0 \leq x \leq 0.10$). Inset indicates the $d\ln\rho/dT^{-1}$ vs. T for $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$	57
4.4	Temperature dependence of AC susceptibility temperature for $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ ($0 \leq x \leq 0.10$) manganites	57
4.5	Plot of $\ln \rho$ versus $T^{-1/4}$ for $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ ($x = 0 - 0.10$) samples. The solid line indicates the best-fit to the variable range hopping (VRH) model	59

- 4.6 Plot of $\ln \rho/T$ versus $1000/T$ for $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ ($x = 0 - 0.10$) samples. The solid line indicates the best-fit to the small polaron hopping (SPH) model

60



LIST OF SYMBOLS AND ABBREVIATIONS

ρ	Resistivity
χ'	Susceptibility
ABX ₃	Perovskite chemical formula
ACS	AC susceptibility
AFM	Antiferromagnetic
A_C	The sum of atomic weight of all cation in the formula unit
A_A	The sum of the atomic weight of all anions in the formula unit
abc	Lattice parameter
Ba	Barium
CMR	Colossal magneto-resistance
Co	Cobalt
Co ³⁺	Cobalt (III) ion
CO	Charge-order
CO ₂	Carbon dioxide
Cr	Chromium
D	Density
D_x	Powder density
DE	Double-exchange
FMM	Ferromagnetic metallic
$h\ k\ l$	Miller indices
JT	Jahn-Teller
K ⁺	Potassium ion
K ₂ CO ₃	Potassium carbonate
Li ⁺	Lithium ion
Mn ³⁺	Magnesium (III) ion
Mn ⁴⁺	Magnesium (IV) ion
MnO ₂	Manganese (IV) oxide
MnO ₆	Manganese oxide octahedral

MI	Metal-insulator
n'	The number of formula units within the unit cell
Na^+	Sodium ion
Na_2CO_3	Sodium carbonate
Nd	Neodymium
Ni	Nickel
Nd_2O_3	Neodymium (III) oxide
O^{2-}	Oxide ion
PMI	Paramagnetic insulating
PM	Paramagnetic
$\langle r_A \rangle$	Average ionic radius
Sr^{2+}	Strontium ion
SEM	Scanning electron microscope
SPH	Small polaron hopping
T	Temperature
T_C	Curie temperature
T_{CO}	Charge-order temperature
T_{MI}	Metal-insulator transition
T_N	Neel temperature
VRH	Variable range hopping
V	Unit cell volume
W_{air}	Weight in air
$W_{acetone}$	Weight in acetone
XRD	X-ray diffraction

LIST OF PUBLICATIONS

1. Razali, S. A., Ibrahim, N., Shamsuddin, S., & Noh, M. Z. (2018). Observation of charge ordering signal in monovalent doped $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ ($0 \leq x \leq 0.10$) manganites. *International Journal of Engineering & Technology*, 7(4.30)85-88.

Scopus

2. Mannan, N. N., Razali, S. A., Shamsuddin, S., Noh, M. Z., & Mohamed, Z. (2018). Effect of Co^{3+} substitution on electro-magnetic properties of $\text{Pr}_{0.75}\text{Na}_{0.25}\text{MnO}_3$ and $\text{Nd}_{0.75}\text{Na}_{0.25}\text{MnO}_3$ manganites. *International Journal of Engineering & Technology*, 7(4.30)389-392.

Scopus

3. Mannan, N. N., Razali, S. A., Shamsuddin, S., & Noh, M. Z. (2017). Crystalline phase, surface morphology and electrical properties of monovalent-doped $\text{Nd}_{0.75}\text{Na}_{0.25}\text{Mn}_{x-1}\text{Co}_x\text{O}_3$. *Journal of Science & Technology*, Vol. 9 No. 3 65-69.

CHAPTER 1

INTRODUCTION

1.1 Background of study

In the last decade, extensive research has been carried out toward the understanding of the extraordinary structural, magnetic, electrical and thermal transport properties of doped perovskite-type manganites with general formula $R_{1-x}A_xMnO_3$ (where R is rare earth metal and A is monovalent/divalent alkali metal). The interest is based on fundamental physics and chemistry due to their high chemical stability, sample preparation methods, doping dependence of their magnetic transition temperature (Zhang *et al.*, 2013), potential application in electronic devices (Phan *et al.*, 2014, Gdaïem *et.al*, 2016) and the complex magneto-electrical as well as colossal magneto-resistance (CMR) properties (Shamsuddin *et al.*, 2013; Malik *et al.*, 2014, Pollert *et. al*, 2004).

The percentage amount of divalent and monovalent cation ions, size of ionic radii are said to have a great influence on the magnetic and transport properties of perovskite material (Akyol *et al.*, 2017). Several reports showed that substitution of a small amount of transition metal element at Mn-site can influence the magnetic and electrical transport properties of manganite compound. However, elemental substitution at A-site also gives extensive impact on the properties of the manganites compound due to the changing of electron bandwidth and the size mismatch, controlled by A-site cation average size (Koubaa *et al.*, 2009). On top of that, it was mentioned the relationship between magnetic and transport properties of this oxides can be well elucidated by using the mechanism of double exchange (DE) of the Mn^{3+}

and Mn^{4+} . On the other hand, observation of surface morphology studies in manganites has been suggested as a successful tool in providing valuable information such as grain size and grain boundaries as well as porosity, which can help to show the interaction between morphological and structural study.

The electrical analysis also plays an important role in providing a better understating the variation of electrical resistivity in the material (Masroor *et al.*, 2016) that describe the electron scattering model and hopping model for metallic and insulating part respectively. To further understand the variation of resistivity behavior in monovalent/divalent doped manganites at the metallic region with zero magnetic field applied, the resistivity data was fitted using a theoretical model. Research proved that resistivity behavior in some manganites is due to combination of weak electron localization and some scattering mechanisms, such as electron-electron, electron-magnon and electron-phonon scattering processes in ferromagnetic phase (Ibrahim *et al.*, 2010). The phase transition of ferromagnetic-paramagnetic with the increased of dopant content occurs when the charge ordered state was weakened. The measurement of the electrical resistivity at low temperature showed the increase in tolerance factor in which indicates the reduction in MnO_6 distortion while enhancing the interaction of DE. Alternatively, in order to understand clearly the electrical analysis at the insulating region, the resistivity data are fitted using two different hopping models, namely, variable range hopping (VRH) and small polaron hopping (SPH). VRH models describe the electrical analysis in manganite based on doping-induced disorder caused by the random distribution of defects, while SPH model implies the existence of strong electron-phonon coupling caused by the Jahn-Teller lattice distortion (Rozilah *et al.*, 2017).

As for that, manganites are manganese oxides material that has their own specialties behavior and one of convenient magnetic ceramic material working at low temperature. Properties of manganites can be altered by some factors, and this study focus on doping factor. Currently, researchers had studied the effect of doping agent on the magnetic and electrical transport of perovksite-manganites structure. Previous study has investigated the effect of Chromium (Cr) doping at Mn-site manganites on the charge-order (CO) state, magnetic and electrical properties of $\text{Nd}_{0.75}\text{Na}_{0.25}\text{MnO}_3$ manganites (Zhang *et al.*, 2011). However, the study on the effect of monovalent doped manganites at A-site to charge ordering is still limited. Hence, as a

consequence, this study reports on the DC electrical resistivity and AC susceptibility measurement on $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ ($0 \leq x \leq 0.10$) manganite with the aim to investigate the effect of partial K-doped on electrical transport and magnetic properties as well as provide an understanding of CO in the material. Results from X-ray diffraction (XRD) and scanning electron microscopy (SEM) measurement as well as values of density and porosity are also presented and discussed.

1.2 Problem statement

Among rare earth element family, Nd based manganites, $\text{Nd}_{0.75}\text{Na}_{0.25}\text{MnO}_3$, has caught attention as it displays the existence of charge ordered at T_{CO} at the area below 170 K (Nabilah *et al.*, 2017; Tang *et al.*, 2008). Attractively, by substituting a small amount of charged ions at A/B-site, the properties of a material will be altered. For instance, study on $\text{La}_{0.7}\text{Nd}_x\text{Ba}_{(0.3-x)}\text{MnO}_3$ showed particles are not fully-densified which would be attributed to the large atomic radius and consequently the high activation energy of Ba atom for the parent compound, but Nd substitution at A-site causes a significant decrease in the grain size (Gokhan Unlu *et al.*, 2016). Besides that, Maryam *et al.*, 2018 revealed that the parent compound of $\text{Nd}_{0.75}\text{Na}_{0.25}\text{MnO}_3$ exhibited insulating behavior. Then, when small amount of Ni was substituted at Mn-site, it was induced to metallic behavior suggesting by weakened of CO state and enhancement double-exchange (DE) mechanism. As stated by Li *et al.*, 2004, the interaction of double exchange on perovskite-base manganites doped with monovalent alkali earth metal cation ions is much stronger compared to divalent alkali earth metal. In the last past decade, there were a few pioneer work conducted on mixed-valent manganite doped with monovalent cation ions such as Na^+ , K^+ and Li^+ . Lanthanum-based manganites doped with Potassium (K), $\text{La}_{0.7}\text{Sr}_{0.3-x}\text{K}_x\text{MnO}_3$, make a transition from paramagnetic to ferromagnetic transition at low temperature and thus show that potassium doping decrease Curie temperature, T_c and lead to DE interactions (Koubaa *et al.*, 2009). Besides, based on Rozilah *et al.*, 2017, AC susceptibility measurement for parent compound of $\text{Pr}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ manganite showed a paramagnetic behavior, then initially weakened CO when a small amount of K^+ ($x = 0.05-0.10$) was doped. By further increasing up to $x = 0.15-0.20$, the CO state was successfully suppressed and inducing ferromagnetic-paramagnetic

transition with Curie temperature, T_c increased with x content. For electrical resistivity measurement, $x = 0$ sample exhibit as insulating behavior, then by increasing amount of K^+ , samples showed metal-insulator transition as transition temperature, T_{MI} increased suggested due to the enhancement of double exchange interaction. However, most of the substitution does not show full suppression of CO-AFM phases probably due to dopant level. As such, the influence of magnetic ions on host composition need to be further investigated to understand the role of the magnetic ions in the CO phase. Hence, magnetic and electrical resistivity properties measured at low temperature would be very interesting to study as this could reveal the information of CO state in the sample as well as provide a better understanding on the properties when other element was substitute at A-site of the compound. In addition, analyze of the electrical resistivity data will give a better understanding of the hopping process in this compound.

1.3 Objectives of study

The objectives of this research are:

- i. To determine the structure and surface morphology of $Nd_{0.75}Na_{0.25-x}K_xMnO_3$ by using powder X-ray diffraction (XRD) and scanning electron microscope (SEM) measurement respectively.
- ii. To investigate the influence of K-doped on magnetic and electrical transport properties of $Nd_{0.75}Na_{0.25-x}K_xMnO_3$ at a lower temperature using AC susceptibility (ACS) and DC electrical resistivity measurement respectively.
- iii. To explain the electrical behavior of $Nd_{0.75}Na_{0.25-x}K_xMnO_3$ manganites using variable range hopping (VRH) and small polaron hopping (SPH).

1.4 Scope of study

This study covers the roles of monovalent cations ion, Potassium (K^+) doped on $Nd_{0.75}Na_{0.25-x}K_xMnO_3$ manganites which have been synthesized by using conventional solid state reaction method. This method involves the process of mixing, grinding, calcined, pelleting and sintering in order to complete the preparation process. The crystalline phase of the manganite compound was carried out at room temperature using X-ray diffraction (XRD) measurement. Observation of the surface morphology was obtained by scanning electron microscope (SEM) measurement at room temperature. The magnetic measurement was analyzed using AC susceptometer with the temperature at range 50K to 300K. Electrical transport properties were performed at a temperature range of 50K - 300K using a DC electrical resistivity measurement utilized using the four-point-probe method. For further understanding, analysis of electrical analysis also carried out using the VRH and SPH model to propose suitable model in explaining the electrical resistivity data.

1.5 Significance of study

Rare-earth manganites perovskite structure are very special due to their interesting physical and magnetic properties. It is capable to dope with other elements to change their properties as well as increasing performance toward the application of magnetic sensor, communication and transportation. By doping process such as K^+ on $La_{0.8}Cd_{0.2-x}K_xMnO_3$ manganite it showed increasing of electrical properties and enhancement of magnetic properties by shifting the transition temperature of T_{MI} and T_C (Dhahri *et al.*, 2010). This study is important as the substitution of Potassium (K) ion at A-site for $Nd_{0.75}Na_{0.25-x}K_xMnO_3$ sample will reveal the influence of the substitution on the structure, magnetic and transport properties. Generally, small amount substitution of a monovalent or divalent ion at A-site of rare-earth manganites will influence the physical properties of the materials, thus substitution of alkaline ions in this Nd-based significantly induced the magnetic properties from ferromagnetic to paramagnetic phase and the electrical properties which are metal-insulator (MI) transition at low temperature measurement. This phenomenon occurred suggestively due to the presence of charge-ordered phase which closely

related to the size of the ionic radius doping agent that affected the average size of A-site cation, electron-bandwidth and the Mn-O-Mn bond angle. This study also important to describe the mechanism in $\text{Nd}_{0.75}\text{Na}_{0.25}\text{MnO}_3$ manganites. In addition, this study also provided additional information and knowledge about CO by providing the information related to the mechanism and properties of manganites. Apart from that, it also provides additional knowledge about the electrical properties by proposing a suitable model in explaining the electrical data where the electrical resistivity data were fitted using the VRH and SPH model.



CHAPTER 2

LITERATURE REVIEW

2.1 Introduction

In this research study, perovskite-type manganite ($R_{1-x}A_x\text{MnO}_3$) is used as the main compound where R is a trivalent ion that includes (La^{3+} , Pr^{3+} , Nd^{3+}). Meanwhile, A stand for ion from group one (monovalent ion) or group two (divalent ion) which include of (Ag^+ , Na^+ , Li^+) and (Ca^{2+} , Sr^{2+} , Ba^{2+}) respectively. Rozilah *et al.*, 2017 in the research study, state that perovskite-type manganites possess its own unique properties such as structure transformation, metal-insulator (MI), charge ordering (CO), and Colossal Magnetoresistance (CMR). All the properties come from the interaction between two ions which are Mn^{3+} and Mn^{4+} . The interaction of Double Exchange (DE) between those two ions will generate ferromagnetic metallic (FMM) state while Jahn-Teller will provide paramagnetic metal insulator (PMI) transition.

In this research study, the monovalent element which is potassium was used to dope with the parent compound of $\text{Nd}_{0.75}\text{Na}_{0.25-x}\text{K}_x\text{MnO}_3$ to see if there are any transition of ferromagnetic-paramagnetic transition or metal-insulator phenomenon. The previous study stated that the monovalent elements are commonly known as the function to convert twice more Mn^{3+} to Mn^{4+} ion compared to divalent elements (Thaljaoui *et al.*, 2014a; Thaljaoui *et al.*, 2014b). Many previous studies was reported about the influence of potassium doped manganite on the structural and electrical properties. Rozilah *et al.*, 2017 in the previous study stated that with the substitution of the potassium ($x = 0, 0.05, 0.10, 0.15$) has weakened the CO state

and actuated the ferromagnetic-paramagnetic transition above Curie temperature T_C . This statement is also supported by Thaljaoui *et al.*, 2014b, saying an increase in potassium substitution content a shift paramagnetic to the ferromagnetic transition temperature is showed. The substitution of potassium increase the unit cell volume of a compound. Moreover, Koubaa *et al.*, 2009a and Koubaa *et al.*, 2009b state that the unit cell volume of the samples was increase when there is an increase in the potassium content. As stated before, the increase in quantity of potassium doped induce a sharp transition from paramagnetic to ferromagnetic and at the same time this substitution leads to a decrease in the Curie temperature, T_C . In simple word, based on the previous study the magnetic measurement observed on the potassium doped manganites have been exhibits a transition from paramagnetic to ferromagnetic with decreasing temperature.

From previous study of $\text{La}_{0.7}\text{Sr}_{0.3-x}\text{Na}_x\text{MnO}_3$ doped with Na, electrical investigation shows that the sample exhibit semiconducting behavior at high temperature while at low temperature it behave metallic-like. Besides, according to Koubaa *et al.*, 2009b, when monovalent element use as the dopant agent, it lead to the increase of Mn^{4+} and the double exchange interaction between $\text{Mn}-\text{O}-\text{Mn}$ angle became weakened. Another way to alter the properties is by doping other transition metal ions on the Mn-site (B-site). As stated by Nabilah *et al.*, 2017 the action of doping Co element at Mn-site of the $\text{Nd}_{0.75}\text{Na}_{0.25}\text{MnO}_3$ modified the properties and give beneficial information of charge-ordered (CO) state. The result from the electrical transport properties analyze by the four-point-probe method, it shows that all the samples ($y = 0 - 0.05$) display insulating behavior in the temperature range of 80 K – 300 K. All the resistivity slope of insulating samples show a minimal change at the temperature of 200K. It also stated that the localization peak of analyzation $d\ln\rho/dT^{-1}$ occured within charge ordering transition from low to higher temperature. For certain condition, manganites can reveal metallic characteristic by applying a high magnetic field and it has been suppressed the charge-ordered state (Li *et al.*, 2006). As for half-doped $\text{Pr}_{0.5}\text{Ca}_{0.5}\text{MnO}_3$ with doping element such as Mg^{2+} , Al^{3+} , Fe^{3+} , Ti^{4+} and Sn^{4+} it was shown to remain as insulating compound until there is an applied magnetic field of 7 T. A metal-insulator transition. This occur due to the compound having magnetic

field result in the to weakening of CO state, which is contrast to the parent compound of $\text{Pr}_{0.5}\text{Ca}_{0.5}\text{MnO}_3$ (Raveau *et al.*, 1997)

2.2 Structure of ceramic

2.2.1 Crystal structure

The crystal structures for those ceramic materials that have predominantly ionic atomic bondings are being composed of electrically charged ions instead of atoms. It involves all the ions that consist in that material which is positively charged metallic ions (cations) that give up their valence electrons to the nonmetallic ion (anions) that carried negative charged. The crystal structure can be influenced by two different characteristics of the component ions in crystalline ceramic materials. The first characteristic which is the magnitude of the electrical charge on each of the component ions, it means that the crystal must be electrically neutral. All the ions have to complement each other to achieve this charge balance for both cation positive charged and anion negatively charged. The second criterion involves the relative sizes of the cations and anions. Basically, cations are ordinarily smaller than anions and consequently the ratio is less than unity because the metallic elements give up electrons when ionized. Each cation prefers to have as many nearest-neighbor anions as possible, same goes to anions that also desire a maximum number of cation nearest neighbors. At the end of this, the stability can be explained by a crystal lattice of material. These ceramic crystal structures become stable when the surrounding of anions all in contact with that cations as illustrated in Figure 2.1.




Figure 2.1: Stable and unstable anion–cation coordination configurations.

2.2.2 Crystal lattice

The concept of crystal lattice was an interpretation of the diffraction pattern of the regular atomic array which pioneered by Lawrence and William Bragg. The position of atoms in the crystal must be at a fixed distance from one another. The interatomic separation constituted an array of lattice vectors defined as the elementary unit cell of volume. These parameters are displayed the symmetry elements in bulk crystal.




Figure 2.2: Schematic representation lattice parameters of a cubic unit cell (Brandon & Kaplan. 2001)

Lattice defined as a set of periodic points in space. (a, b, c) are the three coordinates length indicated by placing the origin at lattice points. The angles are (α, β, γ) subtended by lattice axes illustrated in Figure 2.2. Seven crystal systems are generated from the different values of (a, b, c) and (α, β, γ) namely triclinic, monoclinic, orthorhombic, tetragonal, rhombohedral, hexagonal and cubic (Frank. 2009, Brandon & Kaplan. 2001). The structure of crystalline materials could be confirmed using powder X-ray diffraction technique. The analysis conducted

REFERENCES

- Abdelmoula, N., Dhahri, E., Fourati, N., & Reversat, L. (2004). Monovalent Effects on Structural, Magnetic and Magnetoresistance Properties in Doped Manganite Oxides. *Journal of Alloys and Compounds*, 365(1–2), 25–30.
- Abdel-Latif, I. A. (2012). Rare Earth Manganites and their Applications. *Journal of Physics*, 1(3), 15–31.
- Akyol, M., Akça, G., Ayaş, A. O., Çetin, S. K., & Ekicibil, A. (2017). Effect of Monovalent Cation Doping on Structural, Magnetic, and Magnetocaloric Properties of $\text{Pr}_{0.85}\text{A}_{0.15}\text{MnO}_3$ (A = Ag and K) Manganites. *Journal of Superconductivity and Novel Magnetism*, 30(6), 1515–1525.
- Altintas, S. P., Mahamdioua, N., Amira A., Terzioglu, C. (2014). Effect of anionic substitution on the structural and magneto-electrical properties of La–Ca–Mn–O perovskite manganites. *Magnetism and Magnetic Material*, 368, 111–115.
- Bejar, M., Dhahri, E., Hlil, E. K., & Heniti, S. (2007). Influence of A-site cation size-disorder on structural, magnetic and magnetocaloric properties of $\text{La}_{0.7}\text{Ca}_{0.3-x}\text{K}_x\text{MnO}_3$ compounds. *Journal of Alloys and Compounds*, 440, 36–42.
- Chand, U., Yadav, K., Gaur, A., & Varma, G. D. (2010). Effect of Different Synthesis Techniques on Structural, Magnetic and Magneto-transport Properties of $\text{Pr}_{0.7}\text{Sr}_{0.3}\text{MnO}_3$ Manganite. *Journal of Rare Earths*, 28(5), 760–764.
- Chen, H. Z., Young, S. L., Shi, J. B., Chen, Y. C. (2000). Structure and properties of $\text{La}_{0.7}\text{Pb}_{0.3}\text{Mn}_{1-x}\text{Co}_x\text{O}_3$. *Physica B*, 284(288), 1430–1431.
- Deac, I. G., Tetea, R., & Burzo, E. (2007). Structural, electrical and magnetic properties of perovskites $\text{La}_{0.67}\text{Ca}_{0.33}\text{Mn}_{1-x}\text{Co}_x\text{O}_3$ (0.5~1). *Journal of Magnetism and Magnetic Materials*, 310(2 SUPPL. PART 3), 1972–1974.
- Gamari-Seale, H., Troyanchuk, I. O., Sazonov, A. P., Stefanopoulos, K. L., & Toebbens, D. M. (2008). Structure and magnetic order in $\text{La}_{0.7}\text{Ca}_{0.3}\text{Mn}_{0.5}\text{Co}_{0.5}\text{O}_3$ and $\text{La}_{0.8}\text{Sr}_{0.2}\text{Mn}_{0.5}\text{Co}_{0.5}\text{O}_3$ perovskites. *Physica B: Condensed Matter*, 403(17), 2924–2929.

- Gdaiem, M. A., Ghodhbane, S., Dhahri, A., Dhahri, J., & Hlil, E. K. (2016). Effect of cobalt on structural, magnetic and magnetocaloric properties of $\text{La}_{0.8}\text{Ba}_{0.1}\text{Ca}_{0.1}\text{Mn}_{1-x}\text{Co}_x\text{O}_3$ ($x = 0.00, 0.05$ and 0.10) manganites. *Journal of Alloys and Compounds*, 681, 547–554.
- Goldstein, J., Newbury, D., Joy, D., Lyman, C., Echlin, P., Lifshin, E., Sawyer, L., Micheal, J. *Kluwer Academic*. Plenum Publishers: New York. 2003.
- Gupta, M., Kotnala, Khan, R. K., Azam, W., & Naqvi, A. H. (2013). Magnetic, transport and magnetoresistance behaviour of Ni doped $\text{La}_{0.67}\text{Sr}_{0.33}\text{Mn}_{1-x}\text{Ni}_x\text{O}_3$ ($0.00 \leq x \leq 0.09$) system. *Journal of Solid State Chemistry*, 204, 205–212.
- Haque, T., & Kamegashira, N. (2005). Synthesis, structure and properties of $\text{LnMn}_{0.5}\text{Rh}_{0.5}\text{O}_3$ (Ln = rare earth). *Journal of Alloys and Compounds*, 395, 220–226.
- Ibrahim, N., Yahya, A. K., Rajput, S. S., Keshri, S., & Talari, M. K. (2011). Double Metal-Insulator Peaks and Effect of Sm^{3+} Substitution on Magnetic and Transport Properties of Hole-Doped $\text{La}_{0.85}\text{Ag}_{0.15}\text{MnO}_3$. *Journal of Magnetism and Magnetic Materials*, 323(16), 2179–2185.
- Johnsson, M., & Lemmens, P. (2008). Perovskites and Thin Films - Crystallography and Chemistry. *Journal of Physics Condensed Matter*, 20(26), 1–11.
- Koubaa, M., Cheikhrouhou-Koubaa, W., & Cheikhrouhou, A. (2009a). Effect of K Doping on the Physical Properties of $\text{La}_{0.65}\text{Ca}_{0.35-x}\text{K}_x\text{MnO}_3$ ($0 \leq x \leq 0.2$) Perovskite Manganites. *Journal of Physics and Chemistry of Solids*, 70(2), 326–333.
- Koubaa, W. C. R., Koubaa, M., & Cheikhrouhou, A. (2009b). Effect of Potassium Doping on the Structural, Magnetic and Magnetocaloric Properties of $\text{La}_{0.7}\text{Sr}_{0.3-x}\text{K}_x\text{MnO}_3$ Perovskite Manganites. *Journal of Alloys and Compounds*, 470(1–2), 42–46.
- Lakshmi, Y. K., Manjunathrao, S., & Reddy, P. V. (2014). Influence of Rare-Earth Ion Doping on Magnetotransport Behavior of Potassium Doped Manganites. *Materials Chemistry and Physics*, 143(3), 983–990.
- Li, Z. Q., Liu, H., Liu, X. D., Wu, P., Bai, H. L., Sun, C. Q., & Jiang, E. Y. (2004). Competition Between the Double Exchange and Charge Ordering Interactions in the Bandwidth Controlled $(\text{La}, \text{Nd})_{0.8}\text{Na}_{0.2}\text{MnO}_3$ Manganites. *Physica B: Condensed Matter*, 351(1–2), 114–120.

- Li, Z. Q., Zhang, X. H., Li, W. R., Song, W., Liu, H., Wu, P., Bai, H. L., & Jiang, E. Y. (2006). Charge Ordering, Magnetic, Electrical Transport and Thermal Transport Properties of $\text{Nd}_{0.75}\text{Na}_{0.25}\text{MnO}_3$ Manganite. *Physica B: Condensed Matter*, 371(1), 177–181.
- Li, X. G., Zheng, R. K., Li, G., Zhou, H. D., Huang, R. X., Xie, J. Q., & Wang, Z. D. (2002). Jahn-Teller Effect and Stability of the Charge-Ordered State in $\text{La}_{1-x}\text{Ca}_x\text{MnO}_3$ ($0.5 \leq x \leq 0.9$) Manganites. *Europhysics Letters*, 60(5), 670–676.
- Maryam Arifin, Ibrahim, N., Zakiah Mohamed, Yahya, A. K., Nawazish, A. Khan., & Nasir Khan, M. (2017). Revival of Metal-Insulator and Ferromagnetic-Paramagnetic Transitions by Ni Substitution at Mn Site in Charge-Ordered Monovalent Doped $\text{Nd}_{0.75}\text{Na}_{0.25}\text{MnO}_3$ Manganites. *Journal of Superconductivity and Novel Magnetism*, <https://doi.org/10.1007/s10948-017-4521-7>.
- Malik, H., Mahmood, A., Mahmood, K., Yousaf, M., Warsi, M. F., Shakir, I., Wahab, H., Asghar, M., & Khan, M.A. (2012). Influence of cobalt substitution on the magnetic properties of zinc nanocrystals synthesized via micro-emulsion route. *Journal of Ceramics International*, 40(2012), 9439–9444.
- Mantisi, B. (2016). Generation of polycrystalline material at the atomic scale. *Computational Materials Science*, 118, 245–250.
- Mcbride K., Partridge N., Bennington-gray, S. Felton, S. Stella, L. & Poulidi, D. (2017). Synthesis, characterisation and study of magnetocaloric effects (enhanced and reduced) in manganate perovskites, *Materials Research Bulletin* 88, 69–77.
- Mno K., Gamzatov A. G., Aliev, A. M. Khizriev, K. S. Kamilov, I. K. & Mankevich, A. S. (2011). Critical behaviour of $\text{La}_{0.87}\text{K}_{0.13}\text{MnO}_3$ manganite. *Journal of Alloys and Compounds*, 509(33), 8295–8298.
- Mno L. A., Samancioglu, Y. Sarikurkcü, C. Kaynar, B. M. & Yucel, A. (2010). The influence of the sintering temperature on the structural and the magnetic properties of doped manganites: $\text{La}_{0.95}\text{Ag}_{0.05}\text{MnO}_3$ and $\text{La}_{0.75}\text{Ag}_{0.25}\text{MnO}_3$, *Journal of Magnetism and Magnetic Materials* 322(8), 945–951.

- M'nassri, R., Khelifi, M., Rahmouni, H., Selmi, A., Khirouni, K., Boudjade, N. C., Cheikhrouhou, A. (2016). Study of physical properties of cobalt substituted $\text{Pr}_{0.7}\text{Ca}_{0.3}\text{MnO}_3$ ceramics. *Ceramics International*, 42, 6145–6153.
- Modaresi, N., Kameli, P., Salamati, H. (2014). Impact of Co doping on magnetic and electrical properties of $\text{La}_{0.5}\text{Ca}_{0.5}\text{Mn}_{1-x}\text{Co}_x\text{O}_3$ ($0 \leq x \leq 0.05$) manganites. *Magnetism and Magnetic Material*, 365, 107–114.
- Mohamed, H. F. (2017a). Influence of Sodium Doping on the Electrical and Magnetic Properties of $\text{La}_{0.90}\text{Li}_{0.10}\text{MnO}_3$ Manganites. *Journal of Magnetism and Magnetic Materials*, 424, 44–52.
- Mohamed, H. F. (2017b). Phase Diagram, AC Susceptibility and Thermoelectric Power Properties of the $\text{La}_{0.90}\text{Li}_{0.10-x}\text{Na}_x\text{MnO}_3$ Manganites. *Journal of Alloys and Compounds*, 712, 863–869.
- Nabilah, N. M., Razali, S. A., Shamsuddin, S., & Noh, Z. (2017). Crystalline Phase , Surface Morphology and Electrical Properties of Monovalent-doped $\text{Nd}_{0.75}\text{Na}_{0.25}\text{Mn}_{1-y}\text{Co}_y\text{O}_3$. *International Journal Engineering Technology*, 9(3), 65–69.
- Neogi, S. K., Ghosh, R., Paul, G. K., Bera, S. K., & Bandyopadhyay, S. (2009). Effects of Co doping on structural, morphological and transport properties of sol – gel AZO thin films, *Journal of Alloys and Compounds* 487, 269–273.
- Ning, L. (2008). Magneto-Electric Properties of LaMnO_3 with Monovalent Na Element Doping at A Site, *Rare Metal Materials and Engineering* 37(11), 1–6.
- Nor Asmira, Ibrahim, N., Mohamed, Z., & Yahya, A. K. (2018). Effect of Cr^{3+} substitution at Mn-site on electrical and magnetic properties of charge ordered $\text{Bi}_{0.3}\text{Pr}_{0.3}\text{Ca}_{0.4}\text{MnO}_3$ manganites. *Physica B*, <https://10.1016/j.physb.2018.05.020>.
- Panwar, S., Kumar, V., Chaudhary, A., Kumar, R., & Singh, I. (2015). Theoretical study of magneto transport properties of colossal magneto resistive manganites ($\text{Re}_{1-x}\text{A}_x\text{MnO}_3$): A variational treatment. *Solid State Communication*, 223, 32–36.
- Phan, T. L., Dang, N. T., Ho, T. A., Rhyee, J. S., Shon, W. H., Tarigan, K., & Manh, T. V. (2017). Magnetic and magnetocaloric properties of $\text{Sm}_{1-x}\text{Ca}_x\text{Mn}_3$ ($x=0.88$) nanoparticles. *Journal of Magnetism and Magnetic Materials*, 443(2017), 233–238.

- Phong, P. T., Khien, N. V., Dang, N. V., Manh, D. H., Hong, L. V., & Lee, I. J. (2015). Effect of Pb Substitution on Structural and Electrical Transport of $\text{La}_{0.7}\text{Ca}_{0.3-x}\text{Pb}_x\text{MnO}_3$ ($0 \leq x \leq 0.3$) Manganites. *Physica B: Condensed Matter*, 466–467, 44–49.
- Pollert, E., Hejtmánek, J., Jiráček, Z., Knížek, K., Maryško, M., Doumerc, J. P., Etourneau, J. (2004). Influence of the structure on electric and magnetic properties of $\text{La}_{0.8}\text{Na}_{0.2}\text{Mn}_{1-x}\text{Co}_x\text{O}_3$ perovskites. *Journal of Solid State Chemistry*, 177(12), 4564–4568. <https://doi.org/10.1016/j.jssc.2004.09.004>
- Rao, C. N. R., Arulraj, A., Cheetham, A. K., & Raveau, B. (2000). Charge Ordering in The Rare Earth Manganates : The Experimental Situation, 83.
- Raveau, B., Maignan, A., & Martin, C. (1997). Insulator – Metal Transition Induced by Cr and Co Doping in $\text{Pr}_{0.5}\text{Ca}_{0.5}\text{MnO}_3$. *Journal of Solid State Chemistry*, 166(130), 162–166.
- Roy, S., Guo, Y. Q., Venkatesh, S., & Ali, N. (2001). Interplay of Structure and Transport Properties of Sodium-doped Lanthanum Manganite. *Journal of Physics Condensed Matter*, 13(42), 9547–9559.
- Rozilah, R., Ibrahim, N., Mohamed, Z., Yahya, A. K., Khan, N. A., & Khan, M. N. (2017). Inducement of Ferromagnetic-Metallic Phase in Intermediate-Doped Charge-Ordered $\text{Pr}_{0.75}\text{Na}_{0.25}\text{MnO}_3$ Manganite by K^+ Substitution. *Physica B*, 521(June), 281–294.
- Shamsuddin, S., Ibrahim, A. B. M. A., & Yahya, A. K. (2013). Effect of Er Substitution on Ultrasonic Anomaly in $\text{Dy}_{0.5-x}\text{Er}_x\text{Ba}_{0.5}\text{CoO}_3$ Cobaltates. *Ultrasonics*, 53(6), 1084–1088.
- Shamsuddin, S., Supardan, S. N., Ibrahim, A. B. M. A., & Yahya, A. K. (2014). Ultrasonic Anomaly Near the Charge Ordering Transition in Sr-Doped $\text{Nd}_{0.3}\text{La}_{0.2}\text{Ca}_{0.5-x}\text{Sr}_x\text{MnO}_3$ Manganites. *Journal of Superconductivity and Novel Magnetism*, 27(5), 1229–1234.
- Shaikh, M. W., Mansuri, I., Dar, M. A., Varshney, D. (2015). Structural and transport properties of $\text{La}_{1-x}\text{Ag}_x\text{MnO}_3$ ($x = 0.075, 0.1, 0.125$ and 0.15) manganites. *Materials Science and Semiconductor Processing*, 35, 10–21.
- Singh D., & Mahajan, A. (2015). Effect of A-site cation size on the structural, magnetic, and electrical properties of $\text{La}_{1-x}\text{Nd}_x\text{Mn}_{0.5}\text{Cr}_{0.5}\text{O}_3$ perovskites, *Journal of Alloys and Compounds*, 644, 172–179.

- Sr O. M., Na. M., Koubaa, W. C. Koubaa, M. & Cheikhrouhou, A. (2009). Effect of Monovalent Doping on the Structural, Magnetic and Magnetocaloric Properties in $\text{La}_{0.7}\text{M}_{0.2}\text{M}'_{0.1}\text{MnO}_3$ Manganese Oxides (M = Sr, Ba and M'=Na, Ag, K). *Physics Procedia*, 2, 989–996. <https://doi.org/10.1016/j.phpro.2009.11.054>
- Tai, M. F., Lee, F. Y., & Shi, J. B. (2000). Structure and properties of $\text{La}_{0.7}\text{Pb}_{0.3}\text{Mn}_{1-x}\text{Co}_x\text{O}_3$. *Physica B: Condensed Matter*, 284–288, 1430–1431.
- Tang, T., Huang, R. S., & Zhang, S. Y. (2008). Magnetic and magnetotransport properties of $\text{Nd}_{0.75}\text{Na}_{0.25}\text{MnO}_3$ manganite. *Journal of Solid State Communications*, 147(2008), 190–193.
- Tasarkuyu, E., Irmak, A. E., Coskun, A., & Akturk, S. (2004). Structural, magnetic and transport properties of $\text{La}_{0.70}\text{Sr}_{0.21}\text{K}_{0.09}\text{MnO}_3$. *Journal of Alloys and Compounds*, 588 (2004), 422–427.
- Thaljaoui, R., Boujelben, W., Pekała, M., Pekała, K., Antonowicz, J., Fagnard, J. F., Vanderbemden, Ph., Dabrowska, S., Mucha, J. (2014a). Structural, Magnetic and Magneto-Transport Properties of Monovalent Doped Manganite $\text{Pr}_{0.55}\text{K}_{0.05}\text{Sr}_{0.4}\text{MnO}_3$. *Journal of Alloys and Compounds*, 611, 427–432.
- Thaljaoui, R., Boujelben, W., Pekała, M., Pekała, K., Fagnard, J. F., Vanderbemden, P., Donten, M., Cheikhrouhou, A. (2014b). Magnetocaloric Effect of Monovalent K Doped Manganites $\text{Pr}_{0.6}\text{Sr}_{0.4-x}\text{K}_x\text{MnO}_3$ ($x = 0$ to 0.2). *Journal of Magnetism and Magnetic Materials*, 352(1), 6–12.
- Wandekar, R. V., Wani, B. N., & Bharadwaj, S. R. (2009). Crystal structure, electrical conductivity, thermal expansion and compatibility studies of Co-substituted lanthanum strontium manganite system. *Solid State Sciences*, 11(1), 240–250.
- Wang, R., Wang, D., Zhang, Y., & Zheng, X. (2014). Humidity sensing properties of $\text{Bi}_{0.5}(\text{Na}_{0.85}\text{K}_{0.5})_{0.5}\text{Ti}_{0.97}\text{Zr}_{0.03}\text{O}_3$ microspheres: Effect of A and B sites Co-substitution. *Sensors and Actuators*, 190, 305–310.
- Yadav, K., Vaithyanathan, V., Inbanathan, S. S. R., & Varma, G. D. (2012). Magnetic and charge ordering properties of $\text{Bi}_{0.2}\text{Ca}_{0.8}\text{Mn}_{0.9}\text{X}_{0.1}\text{O}_3$ (where X = Ti, Cr, Fe, Co, Ni, Cu). *Alloys and Compound*, 533, 19–24.

- Yang, H., Zhang, P., Wu, Q., Ge, H., & Pan, M. (2012). Effect of monovalent metal substitution on the magnetocaloric effect of perovskite manganites $\text{Pr}_{0.5}\text{Sr}_{0.3}\text{M}_{0.2}\text{MnO}_3$ ($\text{M} = \text{Na}, \text{Li}, \text{K}$ and Ag). *Journal of Magnetism and Magnetic Materials*, 324, 3727–3730.
- Yuksel, J. K., Oleiwi, M. I., Yilgin, R., & Kocbay, A. N. (2012). Effect of chromium addition on the structural, morphological and magnetic properties of nanocrystalline cobalt ferrite system. *Ceramics International*, 38, 6671–6676.
- Zawawi, R. A., Khairulzaman, N. N., & Shamsuddin, S. (2017). Effect of Cr-Doped on Crystalline Phase, Surface Morphology and Electrical Properties of Charge-Ordered $\text{Nd}_{0.75}\text{Na}_{0.25}\text{MnO}_3$. *International Journal Engineering Technology*, 9(3), 45–48.
- Zhang, X., & Li, Z. (2011). Influence of Cr-doping on the Magnetic and Electrical Transport Properties of $\text{Nd}_{0.75}\text{Na}_{0.25}\text{MnO}_3$. *Journal of Rare Earths*, 29(3), 230–234.
- Zheng, G. H., Sun, Y. P., Zhu, X. B., & Song, W. H. (2006). Structure, magnetic, and transport properties of the Co-doped manganites $\text{La}_{0.9}\text{Te}_{0.1}\text{Mn}_{1-x}\text{Co}_x\text{O}_3$ (0~0.25). *Solid State Communications*, 137(6), 326–331.
- Zhou, W., Ma, C., Cao, M., Gan, Z., Wang, X., Ma, Y., Wang, X., Tan, W., Wang, D., & Du, Y. (2017). Large Magnetocaloric and Magnetoresistance Effects in Metamagnetic $\text{Sm}_{0.55}(\text{Sr}_{0.5}\text{Ca}_{0.5})_{0.45}\text{MnO}_3$. *Ceramics International*, 43(10), 7870–7874.